



- NOTES:**
1. ZONES 1 TO 2 CAN ACCOMMODATE TO 31 UNITS.
 2. SIMPLE PLUG IN JUMPER CABLES ARE AVAILABLE FOR CONNECTING DISPLAY CABINETS TOGETHER.
 3. SHOP FLOOR NETWORK CABLE: 2 CORE (RD/BL) 7/0.2 UNSCREENED
 4. FOR STANDARD PC REFER TO DRG 01527.
 5. THE NC100 MUST BE MOUNTED ADJACENT TO THE ONSITE PC CONNECTED USING A STANDARD RS232 9 PIN CABLE MAX LENGTH 2.5m.
 6. THE MODEM MUST BE CONNECTED USING A STANDARD RS232 9-25 WAY CABLE MAX LENGTH 2.5m.
 7. THE MODEM INTERFACE IS ONLY AVAILABLE ON PRODUCT TYPES NC111, NC121, NC131 AND NC140.
 8. ON EARLY MODELS THE NC CONTACT OF RL1 & RL2 MAY NOT BE FITTED.
 9. DIALOUT 'A' IS CONTINUOUS DIALOUT 'B' IS PULSE (SEE APPLICATION NOTES)

JTL SYSTEMS LTD.
.41 KINGFISHER COURT, HAMBRIDGE RD,
NEWBURY, BERKSHIRE, RG14 5SJ
TEL: 01635-263646 FAX: 01635-263647

ISS	DESCRIPTION	APP'D	DATE
3	UPDATED CONNC CONNECTIONS	MJK	08/03
2	ADDED NOTES	MJK	01/03
4	ADDED NOTE 8 & 9	MJK	02/04

TITLE: NC100 COMMUNICATIONS UNIT
EXTERNAL WIRING FOR
TOUCHSCREEN PC CONNECTION

TYPE:

PROJ.	DRG No:	SHT	OF	ISS.
	02854	1	1	4

THIS IS AN UNCONTROLLED COPY - UNLESS STAMPED WITH CONTROLLED COPY STAMP