

ALARM ANNUNCIATOR

AA

The AA is a unit suitable for the display of up to 20 "critical" alarms currently active in the JTL communications unit alarm log.

The unit can operate a siren to attract attention when new alarm conditions are reported and a lamp to show that there are alarms active on the system.

Type AA can also read pushbutton inputs for muting the siren, scrolling through the list of alarms and informing the JTL communications unit that JTL units are about to be switched off for cleaning or maintenance purposes.

Type AA is intended for use as a remote alarm repeater for the JTL communications unit.

FEATURES

- ◆ Message display drive
- ◆ Communications sockets
- ◆ Solid state outputs
- ◆ Non-volatile set-up memory
- ◆ Voltage-free pushbutton inputs
- ◆ Watchdog to ensure reliable operation
- ◆ Maintenance unit socket

HARDWARE

- ◆ Message display drives 1
- ◆ 12 V d.c. outputs 2
- ◆ Voltage free inputs 2



TECHNICAL SPECIFICATION

Input 1	Cleaning / Maintenance pushbutton
Input 2	Mute/Scroll pushbutton
Output 1	Siren control
Output 2	Lamp control
Output rating	100 mA @ 12 V d.c.
Unboxed dimensions (L x W x H)	208 x 88 x 40 mm
Unboxed weight	0.30 kg
Boxed dimensions (L x W x H)	300 x 150 x 120 mm
Boxed weight	3.35 kg
Power supply (standard)	240 V 48-62 Hz
(optional)	110 or 220 V

ORDERING INFORMATION

AA	Printed circuit board only
AA - S	Printed circuit board with siren
AA - SB	Boxed with siren, pushbuttons and display

Power Supply Options:

For 110 V append -110 to order code
For 220 V append -220 to order code

Doc No. 00827 AA_datasheet.wpd Issue 2 Sept 1993

JTL SYSTEMS LTD

Sales: 41 Kingfisher Court, Hambridge Road, NEWBURY, Berkshire, RG14 5SJ
Service: 1 Petre House, Petre Street, SHEFFIELD, S. Yorks, S4 8LJ

Tel: (01635) 263646
Tel: (0114) 256 0908