

CABINET CONTROLLER TIMED DEFROST

ECED

Type ECED is a unit suitable for the control of refrigerated display cabinets where defrosts are controlled locally according to time of day. The unit controls the cabinet temperature by measuring two air temperatures and operating the evaporator liquid solenoid valve.

Up to 12 defrosts per day can be achieved by setting a schedule of defrost start times and durations in the unit. Defrosts are terminated when the temperature of the air leaving the evaporator (or alternatively, the evaporator temperature itself) exceeds an adjustable defrost termination value, or when an adjustable time is reached.

The unit detects and indicates high temperatures. The alarm level and its response time are adjustable. High temperature alarms are cancelled during defrost.

Cabinet temperature together with simple alarm and defrost mode messages can be indicated using a JTL display unit.

Type ECED provides comprehensive alarm reporting, data-logging and remote access when connected to a JTL Communications Unit.

Type ECED is ideal for use with electric defrost or off-cycle defrost systems.

FEATURES

- ◆ Up to 12 timed defrosts per day
- ◆ Default data set-up switches
- ◆ Temperature measurement inputs
- ◆ Non-volatile set-up memory
- ◆ Temperature display drive
- ◆ Watchdog to ensure reliable operation
- ◆ Relay Outputs
- ◆ Battery supported data-logging memory
- ◆ Maintenance unit socket
- ◆ Communications socket
- ◆ Battery supported real-time clock

HARDWARE

- ◆ Temperature probe inputs 4
- ◆ Probe types supported Tempkey or Elm (selectable)
- ◆ Temperature display drives 1
- ◆ Voltage-free contact outputs 2
- ◆ Voltage-free contact inputs 0
- ◆ Data logging memory capacity 350 points on 2 channels



TECHNICAL SPECIFICATION

Temperature probe input 1	Air On
Temperature probe input 2	Air Off
Temperature probe input 3	Evaporator
Temperature probe input 4	Suction Line
Output 1	Liquid valve control (Normally closed valve)
Output 2	Defrost control
Relay output rating	1 A resistive (240 V max).
Unboxed Dimensions (LxWxH)	208 x 88 x 40 mm
Unboxed Weight	0.36 kg
Power supply (standard)	240 V 48-62 Hz (optional) 110 or 220 V

ORDERING INFORMATION

ECED printed circuit board only

Power Supply Options:

For 110 V append - 110 to order code

For 220 V append - 220 to order code

For suitable enclosures see appropriate datasheet.

Doc No. 00841 ECED_datasheet.wpd Issue 3 Sept 1994

JTL SYSTEMS LTD

Sales: 41 Kingfisher Court, Hambridge Road, NEWBURY, Berkshire, RG14 5SJ
Service: 1 Petre House, Petre Street, SHEFFIELD, S. Yorks, S4 8LJ

Tel: (01635) 263646
Tel: (0114) 256 0908