

# 2 CHANNEL KILOWATT HOUR MONITOR

ECPR

Type ECPR is a unit suitable for monitoring up to 2 power channels. The unit monitors each power from a pulsed power input.

The unit accumulates total KWhr and shows average consumption over various periods. It also indicates calculated maximum demand on 30 minute intervals.

Type ECPR provides comprehensive alarm reporting, data-logging and remote access when connected to a JTL Communications Unit.

The ECPR requires an input from a suitable power meter.

## FEATURES

- ◆ Maintenance Unit socket
- ◆ Non-volatile set-up memory
- ◆ Communications socket
- ◆ Watchdog to ensure reliable operation
- ◆ Data-logging memory

## HARDWARE

- ◆ Power inputs . . . . . 2
- ◆ Voltage-free contact outputs . . . . . 0
- ◆ Voltage-free contact inputs . . . . . 2
- ◆ Data logging memory capacity . . . . . 900 points on 4 channels



## TECHNICAL SPECIFICATION

Power increment .....	0.1 - 25 KWhr/pulse
Totalizer capacity .....	9999999.9 KWhr
Unboxed Dimensions (LxWxH) .....	208 x 88 x 40mm
Unboxed Weight .....	0.30 kg
Power supply (standard) .....	240 V 48-62 Hz
(optional) .....	110 or 220 V

## ORDERING INFORMATION

ECPR .....

Printed Circuit board only

### Power Supply Options:

For 110 V append - 110 to order code  
For 220 V append - 220 to order code

For suitable enclosures see appropriate datasheet.

Doc No. 00846 ECPR\_datasheet.wpd Issue 2 Sept 1993

## JTL SYSTEMS LTD

Sales: 41 Kingfisher Court, Hambridge Road, NEWBURY, Berkshire, RG14 5SJ  
Service: 1 Petre House, Petre Street, SHEFFIELD, S. Yorks, S4 8LJ

Tel: (01635) 263646  
Tel: (0114) 256 0908