



For pulsed expansion valve applications incorporating all common defrost types.



- Stand alone or Networked product
- Registered for Enhanced Capital Allowance (ECA)
- Option to control liquid line valve or condensing unit
- Cabinet lighting/night blind control
- Fan control
- Datalogging at board level
- Multiple temperature control (up to 3 temperature ranges)
- Keyswitched case clean mode
- Set up parameters maintained for restart

Product Data

Temperature Control

LCPC controls the display cabinet temperature by measuring 2 air temperatures and operating a pulsed expansion valve, liquid line solenoid valve or condensing unit. The pulsed expansion valve is controlled using a pressure transducer and suction temperature sensor. Up to 3 cabinet operating temperatures can be selected when using the LCPC in conjunction with an LCD9 keyswitched display.

Defrost Control

Defrost can be initiated by JTL network communications, external input or by real time clock within the controller. Suitable for use with all common defrost methods.

In the event of a communications failure, the controller initiates a "learned defrost" strategy or a preprogrammed schedule.

Up to 12 defrosts per day can be scheduled.

Alarms

LCPC will monitor and alarm on high and/or low temperatures and if defrosts are not detected. Temperature alarms are inhibited during defrost and defrost recovery. Alarm parameters and delay periods are configurable on site or remotely.

Datalogging

Provides comprehensive alarm reporting and datalogging when connected to a JTL Network.

Display

Cabinet temperature, defrost and alarm messages can be indicated locally on a JTL display with or without keyswitch operation.

Remote Access

If operating within a JTL Network, alarm parameters and alarm settings can be viewed and adjusted remotely.

Hardware

Temperature sensor inputs	5
Temperature sensor types supported	5 kohm NTC thermistor
Pressure sensor inputs	1
Pressure sensor input (0-7 bar)	4-20 mA
Pressure sensor supply voltage	15 V dc
Pressure sensor load impedance	250 ohms
Temperature display outputs	1
Temperature display types	LCD8 & LCD9
Voltage-free contact outputs	5
Optically isolated high voltage inputs	2 (240 V max)
Datalogging memory capacity	1000 points on 3 channels

Technical Specification

Temperature sensor input 1	Air On
Temperature sensor input 2	Air Off
Temperature sensor input 3	Evaporator
Temperature sensor input 4	Suction Line
Temperature sensor input 5	Energy saving or defrost termination
Pressure sensor input	Suction pressure
Output 1	Blind closed/Lights off
Output 2	Fan Control or heater control
Output 3	Trim heater control
Output 4 (changeover contact)	Defrost control
Output 5 (changeover contact)	Liquid valve or pulsed valve control
Relay output rating	5 A resistive (240 V max)
Input 1	Lighting & Blind override
Input 2	Defrost initiation
Communications port	RS485 2 wire
Communications data rate	4800/38400 baud (auto detected)
Communications protocol	JTL Jnet zone protocol
Unit dimensions unboxed (L x W x H)	208 x 167 x 43 mm
Unit weight unboxed	0.52 kg
Controller dimensions boxed (L x W x H)	248 x 176 x 56 mm
Controller weight boxed	1.56 kg
Power supply (Standard)	230 V 48-62 Hz
(Optional)	110 V

Ordering Information

LCPC	Controller unboxed
LCPC-B	Controller boxed

Power Supply Options:

For 110 V append-110 to order code



This unit conforms with the relevant EU standards when fitted in accordance with its installation instructions.



Doc No. 02203_LCPC_datasheet.pmd Issue 2 Feb 2003

JTL Systems Limited

Head Office	Newbury	tel: 44 (0)1635 263646
Technical Support Centre	Newbury	tel: 44 (0)871 3157535
Monitoring Centre	Newbury	tel: 44 (0)871 3157531