



CONTROL SYSTEMS Backlit LCD Temp. Display LCD13 & LCD14



- Backlit
- Durable moulded plastic design
- Clip fit mounting

Product Data

The LCD13 or LCD14 display is for use with JTL controllers. They display the current operating conditions together with selected alarms. The data displayed is defined in the controller driving the display.

Technical Specification

Display Type	backlit LCD
Material	Moulded plastic (ABS)
Cables.....	CAB55 (for legacy use see below)
Cutout dimensions	Height max 45 mm min 43.4 mm
.....	Width max 90 mm min 88.9 mm
Display depth	25.5 mm
Operating temperature	0 to 60°C
Storage temperature	-25° to +85°C
Humidity	0-95% (non-condensing)

Note these displays are not suitable for installation in the refrigerated environment.

Ordering Information

LCD13 Black	LCD13 (Obsolete)
LCD14 Black	LCD14 (Current)

Legacy cables

Cables for use with controllers with 7 pin DIN display connections.

Models introduced after 1994:

CAB51

For controllers with 5 pin DIN display connections

CAB52

Doc No. 03739-LCD13-LCD14..pmd Issue 1 Oct 2013

JTL Systems Limited

Head Office

Technical Support Centre

Monitoring Centre

tel: 44 (0)1635 263646

tel: 44 (0) 871 3157535

tel: 44 (0)871 3157531